



TIMBAKOTE DECK PRO DATA SHEET

Exterior water based stain - Satin

Timbakote Deck Pro is water based semi-transparent stain designed to protect and enhance the appearance of new and weathered exterior timber from the weather and harsh Ultra violet rays.

Deck Pro is available in a range of twenty four colourfast colours that enhance the natural wood grain & provides waterproofing protection to help prevent warping, splitting and cracking. Deck Pro also contains a fungicide to resist mould damage and discolouration.

RECOMMENDED USES

Timbakote Deck Pro is an ideal coating for new and weathered timber cladding, fences, decks, outdoor furniture and any exterior timber where a sheer natural waterproof stain is required.

SURFACE PREPARATION

New Timber: Surface should be clean and dry, any stains or stencil marks should be removed. All cut edges should be sealed prior to installation.

Oily Resinous timber should be left to weather for 4-6 weeks prior to coating.

Weathered Timber: Apply a sugar soap solution; leave for 10-15 minutes and scrub with a stiff bristle brush. Rinse off with generous amounts of water and allow to dry. Treat a small area at a time, Hose down vegetation prior to application.

APPLICATION

Apply 2 coats of Timbakote Deck Pro with a good quality brush, roller or applicator pad.

If excess stain occurs redistribute to form an even cover to avoid lap marking. Allow 2 hours between coats. Weathered timber will appear darker after application. A trial patch is recommended before you start. In hot weather dampen timber down prior to application to assist with even distribution of the stain. Always keep a wet edge and coat to the natural breaks in the timber.

Any splashes should be removed immediately by wiping with a rag and water.

Reapply at least every 2 years or when the coating looks weathered.

COVERAGE

6-12 sqm per litre depending on porosity of surface, temperature and application technique

DRY TIMES

Depending on such factors as ambient temperatures, humidity levels and air circulation, the general dry times at a spreading rate of 6-12 sqm per litre are:

Touch dry 20 minutes.

Recoat Time 2 hours.

Curing time 14 days

CLEAN UP

All equipment can be cleaned up in water.

SAFETY

Wear impervious gloves and wash coating deposits off skin with soap and water. Moderately irritating to eyes wear splash proof goggles to protect eyes.

Flush eyes immediately with plenty of water if splashes to the eyes occur. If discomfort persists seek medical attention.

Keep out of reach of children.

Ingestion: Give 1- 3 cups of water and seek medical attention.

Timbakote Coatings Limited

P O Box 101366 NSMC, Auckland New Zealand Ph 0800 846225 (0800 TIMBAKOTE)

Email: info@timbakote.co.nz. Website: www.timbakote.co.nz

DISPOSAL

Let residual coating dry by leaving lid off container. Dispose with refuse if permitted by local council. Paint containers are reusable for non-food purposes and recyclable in areas where recycling and collection facilities are available.

NOTE: Every care is taken to ensure that the information provided in this data sheet is accurate. Timbakote® Coatings Ltd is unable to guarantee results as it has no control over the conditions under which products are applied, the substrate or the application methods. The customer has to determine the suitability of the delivered products or information for its intended purpose.